

LUBRICANTS-SEALERS-CHEMICALS

LUBRICANTS S13/1

SEALERS/CHEMICALS S13/2

Lubricants

ENGINE OILS

Most modern oil is unsuitable for older flat tappet cam engines. When catalytic converters came along, the amount of Zinc, Phosphorous, Molybdenum & other additives was reduced to try & increase the life of the catalyst. Unfortunately, this created thousands of camshaft failures across the World, as no one knew in the aftermarket, what was really happening. Now, that is all behind us, as we have solutions to the problem.

If you have fitted a new flat tappet cam, or an engine with this type of cam fitted, [or indeed a performance hydraulic roller cam] then we recommend the running in oil is used [BY1590], together with the break-in oil additive [BY159]. This exceeds the recommended 2000-2500ppm of Zinc and will protect your cam if you follow correct running in procedures for your camshaft. Keep the oil & additive in for at least 250-500 miles.

BY1590 10W/30 Running in oil **£6.66 US qt**

1 US qts = 946ml. 4 US qts = 1 US Gallon.

BY159 Break-in oil additive **£13.31 354ml**

354ml = .375 US qts.

Once the camshaft/engine is properly run in, we recommend using the Comp-Cams performance oil listed below. To be on the safe side, we recommend using 1/3 of a bottle of the break-in oil additive [BY159] per oil change. This will ensure there is enough Zinc [above 2000ppm] per oil change. This will ensure there is enough Zinc [above 2000ppm] per oil change. This will ensure there is enough Zinc [above 2000ppm] per oil change. This will ensure there is enough Zinc [above 2000ppm] per oil change.

BY1595C 15W/50 Performance oil **£9.19 US qt**

1 US qt = 946ml. 4 US qts = 1 US Gallon.

VR1 Racing oil, a high performance oil for high performance driving. Special driving conditions demand a special motor oil, & Valvoline Racing is certainly special. Formulated for ultimate performance in 4-stroke competition engines used in off-road, rally & racing cars. These race proven lubricants have exclusive chemistry to reduce internal friction, enhance power output, minimise foaming, & resist thermal breakdown. This racing oil is also suitable for every-day city & motorway driving. Contains the ZDP package needed for flat tappet cams. Meets API SJ.

AZ11940 VR1 Racing oil 1 litre, 20W-50 **£8.56**

AZ11951 VR1 Racing Oil 5 litre, 20W-50 **£38.86**



TCI MAX SHIFT AUTOMATIC TRANS FLUID

Add shift quality, performance & durability to any Race automatic transmission by simply pouring in TCI Max Shift [ATF] Transmission fluid. Max Shift has been proven to resist viscosity breakdown in even the most demanding race applications. Fully compatible with other brands of mineral ATF. Here are some key features- *Reduces internal friction & heat build up [while promoting clutch lock-up] for increased shift quality & life. Premium fluids developed with ultra-pure base oils resist viscosity breakdown & extend fluid change intervals. Contains exclusive friction eliminating, anti-foaming & extreme heat additives, no other additives or treatments needed. Exceeds Mercon & Dexron performance specifications - check each formula for exact spec.*



BY950610 Race 1 US qt/.946L

£9.56

APPROXIMATE FLUID CAPACITY [US qts-.946L]

[using standard sump pan only]

TORQUE CONVERTERS:

- 13" 5qts
- 12" 4qts
- 11" 3.5qts
- 10" 3qts
- 9" 2.5qts
- 8" 2qts
- 7" 2qts

TRANSMISSIONS:

- Torqueflite 727/904 5qts
- Ford C4 5.5qt
- Ford C6 7qt
- Ford AOD/AODE 6.5qt
- GM Powerglide 4qts
- GM TH350 4qts
- GM TH400 6qts
- GM 4L80E 7.7qt
- GM700R4/4L60E 6qts
- GM200R4 6qts

Moroso Climbing Gear Lube

High performance extreme high pressure gear lube. Uses include manual transmissions & both conventional & posi-traction diffs, that would have used an EP90 gear oil. Contains special clinging agents that provide direct adhesion to all moving parts.



BY34800 1 US qt/.946L

£23.69

Clevite 77 Bearing Guard (assembly lube)

Specially formulated with an extreme pressure rating to provide proper lubrication for internal engine components during assembly and the first crucial moments of operation after engine start up.



BY2800B2 8fl oz//227ml Bottle

£6.00

VALVOLINE ATF MINERAL TRANSMISSION FLUID

Valvoline transmission fluid, is based on premium base oils & advanced additive systems, providing the ultimate protection. The ATF lubricants listed below, are specially designed to meet the needs of specific transmissions, providing superior lubrication & good cold weather performance.

AZ14820 Dexron 3/Mercon 1-litre **£7.86**

Use above fluid for the "Tremec" range of manual gearboxes



Competition Cams Cam Lube

When your engine is built it can sit around for a long time. Oil would gradually run off the cam etc. These products are designed to stick on, to avoid metal to metal contact & excessive wear.

- BY103 Sachet- 5/8fl oz // 18g **£3.00**
- BY102 Tub- 4fl oz // 113g **£8.32**



Permatex Blue RTV Silicone Gasket

The original Blue. Replaces almost any cut gasket. Makes reliable "formed in place" gaskets that resist cracking, shrinking & migrating. Coats pre-cut gaskets to increase reliability. Temp range -65f to 500f intermittent. Resists car & garage fluids & vibration. Suggested application- Rocker covers/ Sumps/ Timing covers/ Auto g/box sump/ Water pumps/ Thermostat housings etc. Sensor safe.

- BY6BR 3oz tube-carded **£5.03**



Comp/Cams V/Spring Protection Lube

Valve train assembly spray. Use before start up & it will help the running in process. This should extend the life of your valve springs.

- BY106 Valvetrain assembly spray **£13.40**



ARP ASSEMBLY LUBRICANT

The lubricant ARP use when testing and calculating torque wrench settings to be used on their fasteners. Other applications- primary assembly lube for engine components, press fitting, gear trains & general machinery. The lubricant is a premium grade moly base w/rust & corrosion inhibitors, & has an effective lubrication range of -30f to 750f, load range: 500,000 PSI.

- BY100-9903 1.69 fl oz // 48 grams **£11.22**



PERMATEX-"THE RIGHT STUFF"

Use for sealing gaskets, or making a gasket. Using the latest elastomeric rubber gasket technology is blowout resistant, & outperforms pre-cut gaskets. As used by GM/Ford, & M.B. Temp range -75f to 450f (-60c to 232c) continuous, 500f (260c) intermittent. Resists ATF, coolant, oil & other garage fluids. Suggested application- Automotive & Marine gaskets, Rocker covers/ Gearbox covers/ Pumps/ Compressors/ Thermostat housings/ Water pumps/ Sumps etc. This stuff is the best!

- BY25224 7oz Pressurized tube **£23.63**



ARPTHREADSEALER

ARP use this when testing and calculating the torque wrench settings to be used on their fasteners. The sealer delivers a flexible leak proof seal in aluminium, steel, s/less steel & plastic against coolants, water, petrol, natural gas and LPG. Seal is PTFE based w/rust & corrosion inhibitors, with an effective range of -30f to 550f, sealant range: 10,000 PSI (pressure).

- BY100-9904 1.69 oz / 48 grams **£14.23**



Energy Suspension- Silicon Grease

Formula 5 prelube is a versatile, waterproof, non melting grease containing teflon. It forms a tough, durable, chemical resistant film of lubricant that prevents metal to metal contact even under severe shock loads.

- BY9-11108G Poly bush lube **£1.50**



ARP FASTENER ASSEMBLY LUBE

ARP Ultra-Torque fastener assembly lube has been designed to reduce tension pre-load scatter & eliminate the need to cycle high performance engine fasteners before final installation. Claimed to give 95-100% of all ARP recommended installation preloads on the first pull, without cycling fasteners before final assembly.

- BY100-9908 .5 fl oz pouch **£2.30**



Valvoline WD & Silicone Sprays

The silicone spray is a light duty lubricant. Leaves no sticky residue, non staining, stops squeaks & sticking, waterproofs & protects, prevents freezing. 1299 WD fluid penetrates, loosens & lubricates. Displaces moisture from any surface.

- AZ54040 Silicone spray 300ml **£3.71**
- AZ54334 1299 WD penetrating fluid **£0.90**



Moroso Ceramic Engine Seal

The best chemical sealer you can buy. Seals & coats cooling system. Seals minor cracks in heads & blocks. Works equally well in aluminium or steel blocks and heads. *Does not work with antifreeze.*

- BY35500 1 US pint// .47 ltr **£22.51**



K&N Recharger Filter Care Service kit

A maintenance system, designed to recharge any washable air filter. Completely restores air flow efficiency so your air filter performs like new.

- BY99-5050 8oz oil / 12oz cleaner **£12.71**



Bars Leaks

Stop leaks, lubricates pump. Works effectively with all anti-freeze.

- BYR-6 5.5fl oz / 163ml **£3.02**



Sealers

Permatex Ultra Blue Gasket Maker

Ultra silicone, eight times more flexible than cork/composite gaskets. Three times more oil resistant, than regular silicones. Temp range -75f to 500f intermittent. Resists car & garage fluids & vibration. Suggested application- Rocker covers/ Sumps/ Timing covers/ Auto g/box sump/ Diff covers etc. Sensor safe, low smell, non corrosive.

- BY77BR 3.35oz tube-carded **£6.85**



MSD Spark Guard Sealer

Stops voltage leaks, eases boot removal and prevents moisture build up.

- BY8804 **£17.32**



Permatex Ultra Copper Gasket Maker

RTV silicone gasket maker. For 4 cyl, turbocharged or high performance engines. The most advanced, high temperature RTV silicone gasket available. Eight times more flexible than cut gaskets. Three times more oil resistant, than regular silicones. Temp range -75f to 700f intermittent. Resists car & garage fluids & vibration. Suggested application- Exhaust manifolds/headers, Rocker covers/ Sumps/ Timing covers/ Water pumps/ Thermostat housings etc. Sensor safe, low smell, non corrosive. Superior adhesion.

- BY101BR 3oz tube-carded **£11.42**



Loctite -572 Thread Sealant [seals & locks]

Use this product where bolts & studs protrude into a water jacket. For instance, Chevrolet head bolts/studs. Cylinder head screw in studs.

- BY572 50ml bottle **£28.62**



Permatex Indian Head Gasket Shellac Compound

The original quality formula. Hard setting, economical sealant. Seals all common gasketing materials in low temperature and low pressure applications. Temperature range -65f to 350f. Resists diesel fuels & most Garage fluids. Suggested applications- Hose connections/ paper & cardboard gaskets.

- BY5J 2oz bottle **£3.22**



Chemicals etc

Autometer Pro-Comp Gauge Fluid

This is the fluid Autometer put in all their liquid filled instruments



BYAJG485 Small bottle

£9.79

Permatex -271 Threadlocker

High strength red. Ideal for heavy duty applications. Permanently locks studs & press fit items. Adds 3000psi holding power on slip & press fit assemblies. Replaces set screws & circlips. May require special tools for removal. Suggested applications: Cylinder block & rocker arm studs, ring gear bolts, chassis bolts, shock absorber bolts.



BY27100 6ml tube carded

£7.40

Permatex -242 Threadlocker

Medium strength blue. Ideal for all nut & bolt applications 1/4" to 1". Locks & seals. Helps prevent corrosion. Suggested applications: Rocker cover bolts/ water pump bolts/ sump bolts/ drive shaft bolts/ carb studs/ rocker adjustment nuts.



BY24200 6ml tube carded

£6.00

Moroso Block Filler

Just fill with water, mix & pour into block before machining. Helps prevent thin cylinder walls from cracking, & improves ring seal by keeping cylinders round. Dampens unwanted vibrations. Has expansion rate very similar to cast iron. For Drag Racing. Enough for 1 engine.



BY35570 Case of 4 US Gallon containers **£70.02**

Paint- Aerosol-312g

Armor paints. Beware, these tins are under pressure, and the vapours are extremely flammable. Keep away from children.

BYA102	Alum Hi-temp >1200f	£10.74
BYA114	Black Hi-temp >1200f	£10.12
BYA84	Black-engine enamel	£7.66
BYA85	Chevy Orange-eng enamel	£7.66
BYA87	Ford Blue-engine enamel	£7.66
BYA89	Ford Dark blue engine enamel	£7.66
BYA94	Chrysler Blue-eng enamel	£5.75

**Teflon Tape**

This skin packaged tape, impervious to fuel and oil, increases the sealing capabilities of all threaded joints. Each roll comes in a plastic container for convenient storage.



BY9608 1/2" x 260" / 12.7 x 6600 mm **£5.47**

Valvoline Carb Cleaner

AZ54100 Spray 18 oz / 500 ml

£5.16

**Winter Chemicals-Valvoline**

AZ56103 Screenwash 1litre-down to -40c **£5.53**

AZ54300 De-Icer 400ml aerosol **£1.50**

AZ808503 Antifreeze-Maxlife 1-ltr **£7.21**

Extended life up to 5yrs. Ideal for higher mileage engines. Reduces scale & deposit formation. Conditions seals, gaskets & hoses.

**Grey Duct Tape**

Many a Car or Racing Car has had a quick repair carried out using "Duct" tape. 2" wide, 60 yards long. A must for every toolbox!



BYD-60 Grey Duct Tape **£5.48**

Permatex Hand Cleaner 1 US Gallon

Biodegradable, waterless, solvent free hand cleaner, containing no harsh chemicals, mineral oils or ammonia. Pure fresh smelling citrus power does the cleaning. Fortified with aloe, lanolin, glycerin, and other skin conditioners.

BY23218	Smooth Lotion with pump	£21.04
BY25218	Fine Pumice with pump	£14.17

